



Aranet4 PRO without display

The air quality monitor without display for indoor environments allows you to track CO₂ concentration, temperature, relative humidity, and atmospheric pressure.

Aranet4 w/o display

Measures carbon dioxide concentration, temperature, relative humidity, and atmospheric pressure

TDSPC205 (EU)
TDSPC2U5 (US, AS)

Sensor performance

	CO ₂ concentration ¹	Temperature	Relative humidity	Atmospheric pressure ²
Range	0 - 9999 ppm	0 - 50 °C (32 °F to 122 °F)	0 - 85 %	600 - 1100 hPa
Resolution	1 ppm	0.1 °C (0.1 °F)	1 %	1 hPa
Accuracy ³	±30 ppm ±3 % of reading ⁴	±0.3 °C (±0.5 °F)	± 3 %	-2 hPa / +3 hPa
Long term drift	N/A ⁵	0.03 °C/year (0.05 °F/year)	0.5 %/year	1 hPa/year
Time constant τ (63 %) ⁶	100 seconds	10 minutes	TBD	instantaneous

Radio parameters

Line of sight range	3 km (1.9 mi)
Supported ISM bands	EU868, RU869 US920, AS923
Transmitter power	14 dBm
Data transmission interval	1, 2, 5 or 10 minutes
Data protection	XXTEA encryption
Compatible base stations	Aranet PRO

General

Ingress protection rating	IP20
Operating temperature range	0 °C to 50 °C (32 °F to 122 °F)
Operating relative humidity range	0% to 85 %
Dimensions	70 x 70 x 24 mm (2.76 x 2.76 x 0.94 in)
Weight ⁷	104 g (3.7 oz)
Enclosure material	Polycarbonate
Included in the box	2 AA alkaline batteries

Power

Type	2 AA batteries	
	Alkaline ⁸	Lithium ⁹
TX interval	Battery lifetime at 20 °C (68 °F) ¹⁰	
1 minute	1.3 years	1.7 years
2 minutes	2.3 years	3.0 years
5 minutes	4.9 years	6.9 years
10 minutes	8.4 years	12+ years

Compliance

CE	Conformité Européenne
IC	Innovation, Science and Economic Development Canada
FCC	Federal Communications Commission (USA)

NB! Aranel4 is not impact resistant. Do not leave the device in the direct sunlight.

¹ CO₂ sensor of the device is calibrated at standard atmospheric pressure. CO₂ readings are pressure compensated and comply with the specifications down to 750 hPa. If the device has to be used at high altitude for a prolonged period of time, manual calibration of the unit should be performed for optimal performance. It is not intended to use the device higher than 4000 m (13 000 ft) above the sea level.

² The device measures absolute pressure, i.e., pressure readings are not compensated for an elevation above the sea level.

³ 95 % of the sensors measure within these typical limits in equilibrium state at the time of sale. For evaluation of the total measurement error long-term drift has to be taken into account.

⁴ CO₂ measurement accuracy is provided for a range 0 ... 5000 ppm, temperature 15 ... 35 °C (59 ... 95 °F) and relative humidity 0 ... 80 %. Accuracy above 5000 ppm is 10 % of reading, but not guaranteed since it is extrapolated from the calibrated range.

⁵ If a drift of the CO₂ measurements occurs, calibration feature of the device should be used. Auto calibration mode is utilizing ABC algorithm whereas Manual calibration mode demands sensor to be exposed to fresh air.

⁶ Time constant is determined at 1 m/s airflow.

⁷ Weight with alkaline Fujitsu Premium LR6G07 AA batteries.

⁸ Fujitsu Premium LR6G07 AA batteries used for tests and calculations.

⁹ Energizer Ultimate Lithium L91 AA batteries used for tests and calculations.

¹⁰ Battery lifetime data has been obtained by mathematical extrapolation and is provided for descriptive purposes only and is not intended to make or imply any guarantee or warranty.